

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (as Used on Label and List)
Dry Palette Body Paint

All Colors

Section I

Manufacturer's name

ShowOffs Body Art LLC.

Emergency Telephone Number

(877)446-5483

Address (Number, Street, City, State and ZIP Code)

2520 Sand Pike Blvd

Telephone Number for Information

(864)895-0870

Pigeon Forge TN 37863

Date Prepared

January 06, 2020

Signature of Preparer (optional)

Section II A—Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))

OSHA PEL

ACGIH TLV

Other Limits
Recommended

% (optional)

There are no ingredients present which, within the current knowledge of the supplier and in the concentration applicable, are classified as hazardous to health or the environment and require reporting in this section.

Section II B—Non Hazardous Ingredients:

Acrylates Copolymer - 25035-69-2

Castor Seed Oil - 8001-79-4

Benonite Clay – CAS 1302-78-9

Ethycellulose - CAS 9004-57-3

Zinc Stearate - 557-05-1

Kaolin – CAS 92704-41-1

May Contain FD&C Pigments: [CI42090, CI77891, CI19140, CI45410, CI77499, CI15850, CI172000, CI77007, CI45380, CI77266, CI77019]

Section III—Physical/Chemical Characteristics

Boiling Point

NA

Specific Gravity (H₂O = 1)

1.24

Vapor Pressure (mm Hg)

2.3 kPa

Melting Point

NA)

Vapor Density (AIR = 1)

NA

Evaporation Rate (Butyl Acetate = 1)

35

Density 10.35

Appearance Medium viscosity liquid of various colors

Section IV—Fire and Explosion Hazard Data

Flash Point (Method Used) 153°F) -TOC

Flammable Limits

LEL

UEL

Extinguishing Media Use an extinguishing agent suitable for the surrounding fire.

Special Fire Fighting Procedures NA

Unusual Fire and Explosion Hazards NA

Section V—Reactivity Data			
Stability	Unstable		Conditions to Avoid
	Stable X		No specific data
Incompatibility (<i>Materials to Avoid</i>)			
Hazardous Decomposition or Byproducts Should not be produced under normal storage and use.			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur X		Store in glass or approved plastic only
Section VI—Health Hazard Data			
Route(s) of Entry	Inhalation? X	Skin? X	Ingestion? X
Health Hazards (<i>Acute and Chronic</i>) May be harmful if swallowed.			
Extended exposure to vapor may cause irritation to the eyes, nose, and throat.			
No known irritation to the skin.			
Carcinogenicity	NTP? NA	IARC Monographs? NA	OSHA Regulated? NA
Signs and Symptoms of Exposure Although rare, watch for headache and irritation to the eyes, nose, or throat.			
Medical Conditions Generally Aggravated by Exposure			
None reported			
Emergency and First Aid Procedures			
Eyes: Flush with water for at least 15 minutes while holding eyelids open.			
Skin reaction: Remove with makeup remover or rubbing alcohol and wash area with soap and warm water.			
Inhalation: Remove to fresh air.			
Section VII—Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material Is Released or Spilled			
Clean up excess with dry cloth. Remove residue with soap and warm water.			
Waste Disposal Method Place in leak-proof container for proper disposal.			
Precautions to Be Taken in Handling and Storing Keep material in leak-proof container. Store in a cool area away from open flame or extreme heat.			
Other Precautions If using in an enclosed environment for an extended period of time, a mask is recommended.			
Section VII—Control Measures			
Respiratory Protection (<i>Specify Type</i>)			
Ventilation	Local Exhaust X	Special	
	Mechanical (<i>General</i>) X	Other	
Protective Gloves NA	Eye Protection NA		
Other Protective Clothing or Equipment NA			
Work/Hygienic Practices Clean spray and storage equipment regularly.			